

Lagerlista legerat tryckkärlsstål

16Mo3 (15mo3)

Sömlösa rör EN 10216-2, leverans i längder á 5 - 7 m
med certifikat EN 10204 / 3.2

<i>YD x tj</i>	<i>DN</i>	<i>Tum</i>	<i>Vikt</i>
21,3 x 3,2 mm	15	1/2"	1,44
26,9 x 3,2 mm	20	3/4"	1,89
31,8 x 5,0 mm	-	-	3,35
33,7 x 4,0 mm	25	1"	2,95
38,0 x 5,0 mm	-	-	4,12
42,4 x 4,0 mm	32	1 1/4"	4,02
44,5 x 5,6 mm	-	-	5,44
48,3 x 4,0 mm	40	1 1/2"	4,37
51,0 x 4,0 mm	-	-	4,66
51,0 x 5,0 mm	-	-	5,74
57,0 x 5,6 mm	-	-	7,19
60,3 x 5,0 mm	50	2"	6,82
60,3 x 6,3 mm	50	2"	8,42
63,5 x 5,6 mm	-	-	8,1
76,1 x 5,0 mm	65	2 1/2"	8,77
76,1 x 7,1 mm	65	2 1/2"	12,24
88,9 x 5,0 mm	80	3"	10,3
88,9 x 8,0 mm	80	3"	16,16
101,6 x 6,3 mm	-	-	15
114,3 x 6,3 mm	100	4"	16,8
114,3 x 10,0 mm	100	4"	26,05

13CrMo4-5

Sömlösa rör EN 10216-2, leverans i längder á 5 - 7 m
med certifikat EN 10204 / 3.2

<i>YD x tj</i>	<i>DN</i>	<i>Tum</i>	<i>Vikt</i>
21,3 x 3,2 mm	15	1/2"	1,44
26,9 x 3,2 mm	20	3/4"	1,89
33,7 x 4,0 mm	25	1"	2,95
42,4 x 4,0 mm	32	1 1/4"	4,02
48,3 x 4,0 mm	40	1 1/2"	4,37
51,0 x 4,0 mm	-	-	4,66
60,3 x 5,0 mm	50	2"	6,82